

Wheel Features

Tread Material:	Nylon	Core Material:	Nylon
Bearing:	Without Bearing	Tread Hardness:	75D±3
Temperature:	-30°C~90°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✓ Injection nylon, high load capacity, high wear resistance
- ✓ No deformation, anti-aging, endurable to humid environment
- ⚠ Dry grinding shaft, low flexibility of rotation
- ⚠ Hard wheel material, it may damage epoxy flooring
- ⚠ Wheel running may cause some noise





Rolling resistance	■ ■ ■ ■ ■	Excellent
Wear resistance	■ ■ ■ ■ ■	Excellent
Operating noise	■ ■ □ □ □	Acceptable
Floor surface preservation	■ ■ □ □ □	Acceptable



Bracket Features

- ✓ Cast aluminum structure, lightweight and tough
- ✓ Support seat can be adjusted by knob, fixed positioning
- ✓ Powder spray treatment, superior anti-rust and anti-corrosion performance, salt spray test over 72 hours

Parameter (mm)	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius
1.5"	50 kg	65	19	73.5	30.5	50.5
2"	250 kg	75	24	86	38	63
2.5"	500 kg	100	30	106.5	44	75
3"	750 kg	100	31	120	52.5	90
4"	1000 kg	100	31	120	52.5	90



Mounting Drawing



Wheel Size (inch)	Wheel Dia. (mm)	Plate Size (mm)	Bolt Center a×b (mm)	Hole Size (mm)	Hole Top (mm)
1.5"	40	55.5×55.5	42×42	6.6	M10
2"	50	73.5×73.5	58×58	7	M12
2.5"	62	90×90	70×70	9	M14
3"	75	95×95	70×70	10.8	M14
3"	75	95×95	70×70	10.8	M14

Product ID

Product Images



Wheel Size

Plate swivel

Plate fixed

1.5"

32A01-1611

32A07-1611

2"

32A02-1612

32A08-1612

2.5"

32A03-1613

32A09-1613

3"

32A04-1614

32A10-1614

4"

32A05-1614

32A11-1614

Product Details

The whole bracket is made by cast aluminum, lightweight and strong.




The adjustment Knob can adjust the support seat, easily and conveniently to fix.



Nylon wheel sheet is integral injection molding, high loading, anti aging.



Powder surface treatment, looks nice, more environmental protection and good anti-corrosion performance.



[English]

