

Wheel Features

Tread Material:	High Strength PP	Core Material:	High Strength PP
Bearing:	Ball Bearing	Tread Hardness:	75D±3
Temperature:	-25°C~80°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ 2 precision ball bearings,flexible rotation
- ✔ Enhanced injection polypropylene,high load capacity,low starting force,economical choice
- ✔ No deformation,anti-aging,endurable to humid environment
- ✔ With metal covers,thread-proof design
- ⚠ Hard wheel material,it may damage epoxy flooring






Rolling resistance	■ ■ ■ ■ ■	Excellent
Wear resistance	■ ■ ■ □ □	Good
Operating noise	■ □ □ □ □	Acceptable
Floor surface preservation	■ ■ □ □ □	Acceptable

Bracket Features


- ✔ Single-piece forged base,fully welded,impact resistance and high load capacity
- ✔ Plane bearing,high load capacity,impact resistance and flexible steering
- ✔ Radial conical bearing,high load capacity and impact resistance
- ✔ Powder spray treatment,superior anti-rust and anti-corrosion performance,salt spray test over 72 hours
- ✔ ON/OFF pedals,stable braking effect,easy to operate
- ✔ Brake part is replaceable,convenient to maintain

Parameter (mm)	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
5"	500 kg	125	50	175	34	97	151
6"	600 kg	150	50	200	38	113	151
8"	700 kg	200	50	248	47	147	175



[English]

Mounting Drawing




Product ID			
Product Images			
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake
5"	35B01-1394	35B03-1394	35B02-1394
6"	35B04-1395	35B06-1395	35B05-1395
8"	35B07-1396	35B09-1396	35B08-1396

Product Details

ON/OFF brake is easy to operate. Brake components can be replaced with screw connecting.



Planar bearings and radial conical bearings, with high loading, impact resistance, flexible in rotation.



Double-sided welding, with 10mm thickened plate and 8mm thickened bracket.



Iron cover looks nice and anti-winding.

