

Wheel Features

Tread Material:	Rubber	Core Material:	Cast Iron
Bearing:	Ball Bearing	Tread Hardness:	85A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ 2 precision ball bearings,flexible rotation
- ✔ Natural rubber material,vulcanized,high rebound
- ✔ Environmental protection,quiet,effectively protect the floor
- ✔ Painted,anti-rust and anti-corrosion
- ⚠ Biodegradable rubber material,recommended to use within 3 year of production for best performance






Rolling resistance	■ ■ ■ □ □	Good
Wear resistance	■ ■ ■ ■ □	Very good
Operating noise	■ ■ ■ ■ ■	Excellent
Floor surface preservation	■ ■ ■ ■ ■	Excellent


Bracket Features

- ✔ Single-piece forged base,fully welded,impact resistance and high load capacity
- ✔ Plane bearing,high load capacity,impact resistance and flexible steering
- ✔ Radial conical bearing,high load capacity and impact resistance
- ✔ Powder spray treatment,superior anti-rust and anti-corrosion performance,salt spray test over 72 hours
- ✔ ON/OFF pedals,stable braking effect,easy to operate
- ✔ Brake part is replaceable,convenient to maintain

Parameter (mm)	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
5"	300 kg	125	48	175	34	97	151
6"	350 kg	150	48	200	38	113	151
8"	400 kg	200	48	248	47	147	175



Mounting Drawing



Product ID			
Product Images			
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake
5"	35B01-1146	35B03-1146	35B02-1146
6"	35B04-1147	35B06-1147	35B05-1147
8"	35B07-1148	35B09-1148	35B08-1148

Product Details

ON/OFF brake is easy to operate. Brake components can be replaced with screw connecting.



Planar bearings and radial conical bearings, with high loading, impact resistance, flexible in rotation.



Concave - convex designed aluminum core hub, lightweight and high strength. The arc wheel is easy to move and effortless.



The natural rubber wheel has high rebound properties to protect the floor. Iron cover looks nice and anti-winding.

