

Wheel Features

Tread Material:	PU	Core Material:	High Strength PP
Bearing:	Ball Bearing	Tread Hardness:	95A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ 2 precision ball bearings, flexible rotation
- ✔ Injection polyurethane, glue-free self lock structure oil resistance, wear resistance
- ✔ Environmental protection, quiet, effectively protect the floor
- ⚠ Not water-proof, humid environment may accelerate aging of the wheel
- ⚠ Biodegradable material, recommended to use within 1 year of production for best performance





Rolling resistance	■ ■ ■ ■ □	Very good
Wear resistance	■ ■ ■ ■ ■	Excellent
Operating noise	■ ■ ■ ■ □	Very good
Floor surface preservation	■ ■ ■ ■ □	Very good


Bracket Features

- ✔ Steel plate pressed and welded, firm and strong
- ✔ Reinforced riveted, close gap, high structural strength
- ✔ Blue galvanized, ROHS/REACH passed, salt spray test over 72 hours
- ✔ Easy to operate, convenient to release the brake
- ✔ Dustproof ring effectively protects grease for long service life

Parameter (mm)	 Capacity	 Wheel Dia.	 Wheel Width	 Total Height	 Offset	 Swivel Radius	 Swivel Radius
4"	250 kg	100	45	145	34	84	148
5"	300 kg	125	48	165	38	101	151
6"	350 kg	150	50	190	44	119	154
8"	400 kg	200	50	240	54	154	173



Mounting Drawing



Product ID						
Product Images						
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Plate swivel brake	Plate swivel brake	Plate swivel brake
4"	35C01-1104	35C04-1104	35C20-1104	35C65-1104	35C03-1104	35C56-1104
5"	35C05-1105	35C08-1105	35C21-1105	35C66-1105	35C07-1105	35C57-1105
6"	35C09-1106	35C12-1106	35C22-1106	35C67-1106	35C11-1106	35C58-1106
8"	35C13-1107	35C16-1107	35C23-1107	35C68-1107	35C15-1107	35C59-1107

Product Details

Fancy riveting has tight clearance, the structure is stable and high strength.



Dust ring can effectively protect dust and grease lubrication.



The surface treatment of bracket is Zinc plated, blue, which can meet the salt spray test for 72 hours. The bracket is curved shape, nice appearance and high strength.



Reinforced wheel ribs, high strength. Bearing cover is nice looking and tight clearance.



[English]

