

Wheel Features

Tread Material:	Rubber	Core Material:	Steel Core
Bearing:	Ball Bearing	Tread Hardness:	65A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ 2 precision ball bearings,flexible rotation
- ✔ Natural rubber material,vulcanized,high rebound
- ✔ Environmental protection,quiet,effectively protect the floor
- ⚠ Pneumatic tyre,need to repump air regularly





Rolling resistance	■ ■ ■ □ □	Good
Wear resistance	■ ■ ■ ■ □	Very good
Operating noise	■ ■ ■ ■ ■	Excellent
Floor surface preservation	■ ■ ■ ■ ■	Excellent


Bracket Features

- ✔ Steel plate pressed and welded,firm and strong
- ✔ Dustproof ring effectively protects grease for long sevice life
- ✔ Environmentally friendly colour galvanized,salt spray test over 48 hours

Parameter (mm)	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	
Wheel Size	8"	150 kg	220	64	256	50	160
	10"	170 kg	260	86	308	60	190



Mounting Drawing



Product ID

Product Images



Wheel Size

Plate swivel

Plate fixed

8"

65A01-1226

65A02-1226

10"

65A03-1227

65A04-1227

Product Details



Wheel axle with reinforcing plate, the strength is upgraded.

CST's Pneumatic inner and outer tires can assurance quality.



Dust ring can effectively protect grease lubrication, avoid dust and other impurities in harsh environment.

