

Wheel Features

Tread Material:	Rubber	Core Material:	Steel Core
Bearing:	Ball Bearing	Tread Hardness:	75A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ 2 precision ball bearings,flexible rotation
- ✔ Natural rubber material,vulcanized,high rebound
- ✔ Blue-white galvanized,anti-rust and anti-corrosion
- ⚠ Biodegradable rubber material,recommended to use within 3 year of production for best performance





Rolling resistance	■ ■ ■ ■ □	Very good
Wear resistance	■ ■ ■ ■ □	Very good
Operating noise	■ ■ ■ ■ ■	Excellent
Floor surface preservation	■ ■ ■ ■ ■	Excellent

Bracket Features

- ✔ Steel plate pressed and welded,firm and strong
- ✔ Stable braking effect
- ✔ High precision screws stem,packaged with protection tube
- ✔ Galvanized,salt spray test over 48 hours

Parameter (mm)					
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset
5"	200 kg	130	40	169	37
6"	250 kg	150	43	192	40




Product ID	
Product Images	
Wheel Size	Threaded stem brake
6"	66A03-1064
8"	66A01-1065

Product Details



The M20 riveted shaft of the national standard screw is a safety guarantee for workers working at high altitude.

Large area welded brake joints have higher strength than riveted construction. Both brake wheel blade, and lock direction.



Steel core wheel hub, rubber wheel surface, mute and anti-corrosion.

